



enoline 4 + 4
TEMP CONTR



enoline 4
TEMP CONTR

THE ENOLINE ELITE, IS THE NEW GENERATION OF ENOMATIC WINE SERVING SYSTEMS WITH IMPROVED TECHNOLOGY AND MONITORING CAPABILITIES, ADVANCED PRESERVATION AND REFRIGERATION, PRECISE PORTION CONTROLLED SERVINGS, COMPACT AND VERSATILE DESIGN, WITH CUSTOMIZABLE OPTIONS AND DIFFERENT COLOURS. AIMED TO PROVIDE A NEW INTERACTIVE WINE SERVICE EXPERIENCE, THE ELITE IS THE PERFECT FIT FOR ANY CONTEMPORARY WINE HOSPITALITY ENVIRONMENT.

enoline

- **Available models:**
 - enoline 4 TC (4 bottles in a row)
 - enoline 4+4 bottle TC (8 bottles in a row)
- **Wine temperature:**
Temperature Controlled: from 7 to 18 °C (from 45 to 64 °F).
The 8 bottles dispenser has a double cooling system (4+4 bottles) so that it can store both red and white wines.
- **Use and system activation:** dispensers can be used either behind the counter (without wine card) or self-service (with wine card).
- **Gas supply :** food nitrogen or argon (cylinder or generator not included).
- **Servings :** 1 or 3 volumes with touch screen key display.
- **Display:** each position has an LCD graphic touch screen interactive display to monitor the dispenser's functions.
A central LCD graphic screen supplies general information.
- **Materials:** stainless steel.
- **Colors and finishings:** In addition to the classic stainless steel finish, it is possible to choose among the following colors: elegant black, pearl white, stone grey, retro cream, and india brown. Pistons and handles also available in golden finish.
- **Cooling system:** by modern Peltier cells (Gas Free).
- **Condensation drainage:** not required (self contained refrigeration).
- **Lighting:** double led lit that indicates the dispenser efficiency level. Lighting changes the intensity according to different functions.
- **Environment control:** a junction box performs a check on allexternal environment conditions (temperature, pressure, humidity) in order to auto-adjust the dispenser's efficiency. This guarantees increased precision of doses and better functionality of the refrigeration system.
- **Nitrogen leak control:** a designated pressure control system highlights any gas leak directly on the display.
- **Bottles lifting system:** electrical pistons that avoid using air or gas for bottle activation.
- **Positioning:** can be lined up on both sides, 10 cm (2") at rear and 25 cm (9.8") on the top needed; support furniture needed.
- **Wine card:** chip card and RFID system.
- **Modules interfacing:** LAN network, TCP/IP protocol.

models	L	H	D	weight	electrical requirements
enoline 4 TC	532 mm (21")	670 mm (26.4")	303 mm (11.9")	45 kg (99.2 lbs)	110 / 220 V. – 250 W.
enoline 4+4 TC	972 mm (38.3")	670 mm (26.4")	303 mm (11.9")	65 kg (143.3 lbs)	110 / 220 V. – 400 W.